



## Mastering energy, time and money

**CIDAN F** is fast, powerful, easy to use and reliable. The robust design has welded sides, extra strong lower beam and clamping beam. The folding beam, dual powered, is exceptionally rigid and stable but at the same time so narrow that the operator doesn't step back when folding.

The machine is generously designed with opening height of 150 mm and the large recesses in the clamping beam, 49 mm high and 57 mm wide, allow greater flexibility. There is also ample height above the straight rail to leave space for completed details.

CIDAN F is the master of fine detail with spring steel gauging fingers and the narrowest folding rail on the market. Get precision, finish and flexibility with easy change folding rail, even for very fine gauge measurements.


Choose a CIDAN F and you choose work satisfaction and productivity in optimal combination.

### The most important advantages:

- ✓ Fast, user friendly and reliable.
- ✓ Adjustable crowning for perfect folding results for any thickness and width.
- ✓ Two folding rails as standard, with 7/10 mm and 15 mm widths.
- ✓ 8–16 gauging fingers depending on model and length required.
- ✓ Choose between two control systems: EasyLink or nuLink.



**Generous and ergonomic.** The opening height is 150 mm. Perfect for fast, efficient and ergonomic profile handling.



**Master of fine detail.** With the CIDAN concept of spring steel gauging fingers and the narrowest folding rail on the market, you get precision, finish and flexibility, even for very fine gauge measurements, down to 3 mm.



Discover the power of **nuLINK**, our state-of-the-art control system designed to revolutionize your production process. nuLINK is more than just a control system – it's your efficient and safe gateway to perfect parts, even in the hands of a beginner sheet metal machine operator.




**Spacious recesses** in the clamping beam. 49 mm high and 57 wide, the recesses allow greater flexibility and make complex folding much easier. With the new F and FS/FX you have new possibilities and can achieve the results you want both faster and trouble-free.



**Adjustable crowning** as standard gives you perfect folding results for any thickness or width every time.



With a simple **rotary shear** attachment along the bend line, you can easily cut off blanks or folded profiles. (Only F41.)

 Find out more about CIDAN F on our demo video: <https://youtu.be/hOjtA7rC8qU>

	Working length	Folding capacity			Opening height	Outer dimensions			Weight	Motor	
	mm (")	Steel <sup>1</sup> mm (ga)	Stainless <sup>2</sup> mm (ga)	Aluminium <sup>3</sup> mm (")	Clamping beam mm (")	Length mm (")	Width <sup>4</sup> mm (")	Height mm (")	kg (lbs)	Clamping beam kW (hp)	Folding beam kW (hp)
<b>F26</b>	2600 (102)	1.75 (15)	1.1 (19)	2.6 (0.102)	152 (5.9)	3658 (144)	1575 (62)	1955 (77)	2502 (5515)	0.75 (1)	1.1 (1.5)
<b>F32</b>	3200 (126)	1.5 (16)	0.9 (20)	2.2 (0.087)	152 (5.9)	4258 (168)	1575 (62)	1955 (77)	2898 (6388)	0.75 (1)	1.1 (1.5)
<b>F41</b>	4100 (161)	1.25 (22)	0.8 (22)	2.0 (0.078)	152 (5.9)	5158 (203)	1575 (62)	1955 (77)	4100 (9038)	1.5 (2)	2.2 (3)

Tensile strength <sup>1</sup>400 N/mm<sup>2</sup> <sup>2</sup>600 N/mm<sup>2</sup> <sup>3</sup>200 N/mm<sup>2</sup> <sup>4</sup>With 1050 mm back gauge.

Dealer

**CIDAN**  
MACHINERY GROUP

CIDAN Machinery Group markets and manufactures CIDAN, Göteneds, Forstner and nuIT

CIDAN Machinery Sweden AB • Box 21 • 533 21 Götene/Sweden • Phone: +46 511-245 20 • [info@cidanmachinery.com](mailto:info@cidanmachinery.com) • [www.cidanmachinery.com](http://www.cidanmachinery.com)